


CHANNEL BRACKETS & CHANNEL LENGTHS RANGE

RANGE SIZE CHARTS




QUICK NUT - SIZE CHART					
Size	Bag Qty	Pack	Part No.		
		Qty	- Ch.		
<u></u>			Accs.		
M8 SZ0860QRN					
M10 SZ1060QRN			1060QRN		

ABOUT THE PRODUCT

M10 PLAIN CHANNEL NUT AND SQUARE PLATE WASHER ASSEMBLY

RANGE SIZE CHARTS



145G M10 TAPPED BEAM CLAMP WITH CONE POINT SET SCREW - SIZE CHART				
Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
NA	100		GB37	

ABOUT THE PRODUCT


Description: 145g M10 TAPPED BEAM CLAMP - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



5 HOLE CROSSPLATE – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
NA	10		GB39		

ABOUT THE PRODUCT


Description: 5 HOLE CROSSPLATE - GALVANISED The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



5 HOLE GUSSET 'T' BRACKET – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
NA	40		GB45		

ABOUT THE PRODUCT


Description: 5 HOLE GUSSET T BRACKET - GALVANISED - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



CHANNEL 'T' BRACKET – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
NA	30		GB46		

ABOUT THE PRODUCT


Description: *GALVANISED CHANNEL T BRACKET* - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



DELTA PLATE BRACKET – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
41 x 21mm	10		GB4721		
41 x 41mm	10		GB4741		
41 x 82mm	10		GB4782		

ABOUT THE PRODUCT


Description: *DELTA PLATE BRACKET* - GALVANISED - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



CANTILEVER ARM – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
150mm	10		G68150		
300mm	10		G68300		
450mm	10		G68450		
600mm	10		G68600		
750mm	10		G68750		
900mm	10		G68900		

ABOUT THE PRODUCT


Description: CANTILEVER ARM - GALVANISED - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



TOP HAT BRACKET – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
41 x 21mm	50		GB4020		
41 x 41mm	50		GB4040		
41 x 82mm	50		GB4080		

ABOUT THE PRODUCT


Description: GALVANISED **TOP HAT BRACKET** - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



EXTERNAL CHANNEL CONNECTORS – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
41 x 21mm	20		GB41A21		
41 x 41mm	20		GB41A41		

ABOUT THE PRODUCT


Description: EXTERNAL CHANNEL CONNECTORS - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



INTERNAL CHANNEL CONNECTORS – WITH FIXING SCREW – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
41 x 21mm	40		GB42A21		
41 x 41mm	40		GB42A41		

ABOUT THE PRODUCT


Description: *INTERNAL CHANNEL CONNECTORS* - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



	DOUBLE FIX BASE PLATES – GALVANISED - SIZE CHART				
П	Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
	NA	40		GB43	

ABOUT THE PRODUCT


Description: - *GALVANISED DOUBLE FIX BASE PLATES* - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



SINGLE FIX BASE PLATES – GALVANISED - SIZE CHART				
Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
NA	40		GB44	

ABOUT THE PRODUCT


Description: GALVANISED SINGLE FIX BASE PLATES - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



2 PIECE CHANNEL CLAMP – PRE GALV. WITH NUT & BOLT - SIZE CHART				
Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
1/2"			G6915	
3/4"			G6917	
1"			G6920	
1 1/4"			G6923	
1 1/2"			G6924	
2"			G6927	
2 1/2"			G6930	
3"			G6933	
4"			G6937	
5"			G6940	
6"			G6942	

ABOUT THE PRODUCT

Description: 2 PIECE CHANNEL CLAMP - Pre Galv. with Nut & Bolt - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE **CHARTS**



CHART	ELNOTTIS - STANDAN	D CAUGE 2.5MM	THERNESS SIZE
Size	Bag Qty	Pack Qty	Part No Ch. Accs.
41 x 21mm		50	CH4121P3
41 x 21mm		50	CH4121P6
41 x 41mm		50	CH4141P3
41 x 41mm		50	CH4141P6
41 x 82mm		25	CH4141P3B
41 x 82mm		25	CH4141P6B

ABOUT THE PRODUCT


Description: PLAIN CHANNEL LENGTHS BS6946:1988 STANDARD GAUGE 2.5mm THICKNESS - PLAIN - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



SLOTTED CHANNEL LENGTHS – STANDARD GAUGE - SIZE CHART			
Size	Bag Qty	Pack Qty	Part No Ch. Accs.
41 x 21mm		50	CH4121S3
41 x 21mm		50	CH4121S6
41 x 41mm		50	CH4141S3
41 x 41mm		50	CH4141S6
41 x 82mm		25	CH4141S3B
41 x 82mm		25	CH4141S6B

Slotted Channel Material: Channel Brackets &

Lengths are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option.

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish.

Channel (Strut) lengths are available in a Pre
Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre-drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

Country of Origin: Channel accessories and bracketry are manufactured in India. Channel (Strut) lengths are manufactured in the UK.


ABOUT THE PRODUCT

SLOTTED CHANNEL LENGTHS

The Slotted Channel Length range and channel brackets are manufactured in accordance with BS6946:1988. The whole range is primarily designed and manufactured to support and fix together channel lengths (Strut) in a metal framework situation. All Channel lengths are manufactured in accordance with BS6946:1988.

Slotted Channel Dimensions - BS6946:1988 STANDARD GAUGE 2.5mm THICKNESS - Slot sizes on Standard gauge are 28 x 14mm. Light gauges are 28 x 11mm.

RANGE SIZE CHARTS




WELDED SHELF BRACKET – GALVANISED - SIZE CHART				
Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
NA	50		GB11	

ABOUT THE PRODUCT

Finishes: *Welded Shelf Bracket* - Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

RANGE SIZE CHARTS




90 DEGREE LARGE DELTA BRACKET – GALVANISED - SIZE CHART				
Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
NA 50 GB12				

ABOUT THE PRODUCT

90 DEGREE LARGE DELTA BRACKET with 2x2 holes - Galvanised

RANGE SIZE CHARTS




120G BEAM CLAMP – GALVANISED - SIZE CHART				
Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
NA	200		GB34	

ABOUT THE PRODUCT

Finishes: 120g BEAMCLAMP - GALVANISED - Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

RANGE SIZE CHARTS




430G M10 TAPPED BEAM CLAMP WITH CONE POINT SET SCREW – GALVANISED - SIZE CHART				
Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
NA 50 GB35				

ABOUT THE PRODUCT

Country of Origin: 430g M10 TAPPED BEAM CLAMP with CONE POINT SET SCREW - GALVANISED - Channel accessories and bracketry are manufactured in India. Channel (Strut) lengths are manufactured in the UK.

RANGE SIZE CHARTS



2×1 HOLE 90 DEGREE ANGLE BRACKET – GALVANISED - SIZE CHART				
Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
96mm x 50mm	100		GB09	
102mm x 42mm	100		GB09A	
57mm x 90mm	100		GB09B	

ABOUT THE PRODUCT


Description: 2x1 Hole 90 Degree Angle Bracket - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



90 DEGREE SMALL DELTA BRACKET – GALVANISED - SIZE CHART				
Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
NA 50 GB10				

ABOUT THE PRODUCT


Description: 90 DEG SMALL DELTA BRACKET - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



2×2 HOLE 90 DEGREE ANGLE BRACKET – GALVANISED - SIZE CHART				
Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
NA 70 GB13A				

ABOUT THE PRODUCT


Description: 2x2 Hole 90 Degree Angle Bracket - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



3×1 HOLE 90 DEGREE ANGLE BRACKET – GALVANISED - SIZE CHART				
Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
NA	NA 50 GB14			

ABOUT THE PRODUCT


Description: 3x1 Hole 90 Degree Angle Bracket - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



90 DEGREE ANGLE LEFT HAND T BRACKET – GALVANISED - SIZE CHART				
Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
NA	60		GB15	

ABOUT THE PRODUCT


Description: 90 DEGREE ANGLE LEFT HAND T BRACKET - GALVANISED - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



90 DEGREE ANG	LE RIGHT HAND T BRA	CKET – GALVANISI	ED - SIZE CHART
Size	Bag Qty	Pack Qty	Part No Ch. Accs.
NA	60		GB16

ABOUT THE PRODUCT


Description: 90 DEGREE ANGLE RIGHT HAND T BRACKET - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



90 DEGREE ANGLE T BRACKET – GALVANISED - SIZE CHART				
Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
NA	50		GB17	

ABOUT THE PRODUCT


Description: 90 DEGREE ANGLE T BRACKET - GALVANISED - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



22.5 DEGREE OBTUSE ANGLE BRACKET – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
NA	50		GB18		

ABOUT THE PRODUCT


Description: 22.5 DEGREE OBTUSE ANGLE BRACKET - GALVANISED - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



M10 BEAM CLAMPS WITH SQUARE U BOLT AND NUTS – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
41 x 21mm	50		GB1921		
41 x 41mm	50		GB1941		
41 x 82mm	50		GB1982		

ABOUT THE PRODUCT


Description: M10 BEAM CLAMPS with SQUARE U BOLT - GALVANISED BEAM CLAMP with SQUARE U BOLT AND NUTS M10 - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



WINDOW BRACKET WITH CONE POINT SET SCREW – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
41 x 21mm	50		GB2021		
41 x 41mm	50		GB2041		
41 x 82mm	50		GB2082		

ABOUT THE PRODUCT


Description: GALVANISED *WINDOW BRACKET with CONE POINT SET SCREW* - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



15 DEGREE OBTUSE ANGLE BRACKET – GALVANISED - SIZE CHART				
Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
NA	50		GB23	

ABOUT THE PRODUCT


Description: 15 DEGREE OBTUSE ANGLE BRACKET - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



45 DEGREE ACUTE 2 HOLE ANGLE BRACKET – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
NA	50		GB24		

ABOUT THE PRODUCT


Description: 45 DEGREE ACUTE 2 HOLE ANGLE BRACKET - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



ACUTE ANGLE 4 H	OLE 45 DEGREE 'T' B	RACKET – GALVAN	NISED - SIZE CHART
Size	Bag Qty	Pack Qty	Part No Ch. Accs.
NA	50		GB25

ABOUT THE PRODUCT


Description: ACUTE ANGLE 4 HOLE 45 DEGREE 'T' BRACKET - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



M10 'C' BEAM CLAMPS TAPPED WITH CONE POINT SET SCREW – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
41 x 41mm 25 GB2641					

ABOUT THE PRODUCT


Description: GALVANISED 'C' BEAM CLAMPS TAPPED M10 c/w CONE POINT SET SCREW - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



SINGLE Z BRACKET – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
NA	100		GB27		

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish.

Channel (Strut) lengths are available in a Pre
Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

Country of Origin: Channel accessories and bracketry are manufactured in India. Channel (Strut) lengths are manufactured in the UK.


The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988.

ABOUT THE PRODUCT

Description: Single Z Bracket - *Galvanized* - These Z Brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. Note we also stock Shallow Z brackets and Double Z Brackets.

Z Bracket Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

RANGE SIZE CHARTS



DOUBLE 'Z' BRACKET – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
NA	50		GB28		

ABOUT THE PRODUCT


Description: *DOUBLE 'Z' BRACKET* - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988. We also stock Shallow Z brackets and Single Z Brackets.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



SHALLOW 'Z' BRACKET – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
NA	100		GB29		

ABOUT THE PRODUCT


Description: SHALLOW 'Z' BRACKET - GALVANISED - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



45 DEGREE OBTUSE ANGLE BRACKET, 2 HOLE – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
NA	50		GB30		

ABOUT THE PRODUCT


Description: 45 DEGREE OBTUSE ANGLE BRACKET, 2 HOLE - GALVANISED - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



ʻZ' BEAM CLAN CHART	IP, M10 TAPPED WITH 10 I	DEGREE PITCH – (GALVANISED - SIZE
Size	Bag Qty	Pack Qty	Part No Ch. Accs.
NA	100		GB31

ABOUT THE PRODUCT


Description: 'Z' BEAM CLAMP, M10 TAPPED with 10 DEGREE PITCH - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



DOUBLE WIDE TOP HAT BRACKET – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
NA 25 GB32					

ABOUT THE PRODUCT


Description: DOUBLE WIDE TOP HAT BRACKET - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



DOUBLE CHANNEL BRACKETS – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
NA	50		GB33		

ABOUT THE PRODUCT


Description: DOUBLE CHANNEL BRACKETS - GALVANISED - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre-drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



DOUBLE CHANNEL BASE PLATE – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
NA	10		GB36		

ABOUT THE PRODUCT


Description: *GALVANISED DOUBLE CHANNEL BASE PLATE* - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



PLAIN CHANNEL NUTS – BZP - SIZE CHART				
Size	Bag Qty	Pack Qty	Part No Ch. Accs.	
M6	100	600	SZ0660/P	
M8	100	600	SZ0860/P	
M10	100	600	SZ1060/P	
M12	100	600	SZ1260/P	

ABOUT THE PRODUCT


Description: PLAIN CHANNEL NUTS - BZP - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Channel Nuts Material: Our Channel Nuts, accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Channel Nuts Finishes: All of our Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



SHORT SPRING CHANNEL NUTS – BZP - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
M6	100	600	SZ0660/S		
M8	100	600	SZ0860/S		
M10	100	600	SZ1060/S		
M12	100	600	SZ1260/S		

ABOUT THE PRODUCT


Description: SHORT SPRING CHANNEL NUTS, BZP - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Short Spring Channel Nuts Material: Channel nuts, accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Short Spring Channel Nuts Finishes: Channel Nuts, accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



LONG SPRING CHANNEL NUTS, BZP - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
M6	100	600	SZ0660/L		
M8	100	600	SZ0860/L		
M10	100	600	SZ1060/L		
M12	100	600	SZ1260/L		

ABOUT THE PRODUCT


Long Spring Channel Nuts Description: BZP - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Long Spring Channel Nuts Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Long Spring Channel Nuts Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



SQUARE PLATE WASHERS – BZP - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
M8	100	400	SZ0842/6		
M10	200		SZ1042/6		
M12	100	400	SZ1242/6		

ABOUT THE PRODUCT


Description: SQUARE PLATE WASHERS - BZP - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



2 HOLE FLAT PLATE BRACKET – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
NA	150		GB02		

ABOUT THE PRODUCT


Description: 2 HOLE FLAT PLATE BRACKET - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



3 HOLE FLAT PLATE BRACKET – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
NA	100		GB03		

ABOUT THE PRODUCT


Description: 3 HOLE FLAT PLATE BRACKET - GALVANISED - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



4 HOLE FLAT PLATE BRACKET – GALVANISED - SIZE CHART					
Size	Bag Qty	Pack Qty	Part No Ch. Accs.		
NA	50		GB04		

ABOUT THE PRODUCT


Description: 4 HOLE FLAT PLATE BRACKET - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



5 F	5 HOLE FLAT PLATE BRACKET – GALVANISED - SIZE CHART					
Size		Bag Qty	Pack Qty	Part No Ch. Accs.		
NA		50		GB05		

ABOUT THE PRODUCT


Description: 5 HOLE FLAT PLATE BRACKET - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



FLAT 'L' BRACKET – GALVANISED - SIZE CHART			
Size	Bag Qty	Pack Qty	Part No Ch. Accs.
NA	100		GB06

ABOUT THE PRODUCT


Description: FLAT 'L' BRACKET - GALVANISED - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

RANGE SIZE CHARTS



1×1 HOLE 90 DEGREE ANGLE BRACKET – GALVANISED - SIZE CHART						
Size	Bag Qty	Pack Qty	Part No Ch. Accs.			
48mm x 50mm	150		GB08A			
57mm x 42mm	150		GB08B			

ABOUT THE PRODUCT

Description: 1x1 Hole 90 Degree Angle Bracket - The Channel Accessory range of bracketry products are manufactured in accordance with BS6946:1988. The brackets are designed and manufactured to primarily support and fix together Channel (Strut) lengths in a metal framework situation. All Channel (Strut) lengths are manufactured in accordance with BS6946:1988.

Material: Channel accessories and bracketry are predominantly made from Mild Steel material, in 6mm thick profile. Channel (Strut) lengths are manufactured from Pre Galvanised Steel to BS EN 10346: 2015 and are available in Standard gauge profile (2.5mm thickness) and also Light gauge profile (1.5mm thickness) and have either a Plain or Slotted option. (Slot sizes on Standard gauge are 28 x 14mm. Light gauge are 28 x 11mm).

Finishes: Channel Accessories and bracketry products are available with a Hot Dipped Galvanised finish. Channel (Strut) lengths are available in a Pre Galvanised finish. Both finishes are readily available from stock. Other finishes are available to order.

Connections / Fixing Methods: The range of Channel accessories and bracketry are predominantly pre drilled with 14mm fixing holes allowing the use of bolts and threaded rod to facilitate fixings.

Country of Origin: Channel accessories and bracketry are manufactured in India. Channel (Strut) lengths are manufactured in the UK.

Every effort has been made to ensure the accuracy of data within these pages. We cannot however be held liable for any discrepancies that may arise between this data and actual product. The dimensions are provided as a guide and we recommend contacting a company representative for confirmation. Greenaway Pipeline Products Ltd reserve the right to make changes without notice at any time.

Sales: 01922 743 322

Email: enquiries@greenaways.co.uk **Web:** https://greenaways.co.uk